



# Safety Data Sheet

REMA TIP TOP

Product #: 517 9008

SDS #: RTT-IND-038

Rev. # 5

Rev. Date: 2/22/2017

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** T2 Solution A4 (CFC free)

**Chemical Family:** Ester & Aromatic Hydrocarbon Solution

**Product Use:** Adhesive

**Restrictions on Use:** Use as directed by manufacturer

**Manufacturer:** Rema Tip Top - North America  
119 Rockland Ave.  
Northvale, NJ 07647  
Phone: 201 256-8200

**24-Hour Emergency Phone Number:** North America: 800-424-9300 (CHEMTREC)  
International: 703-527-3887 (CHEMTREC) Collect Calls Accepted

## 2. HAZARD IDENTIFICATION

### GHS Classifications

#### **Health Hazards**

Skin Irritation, Category 2

Eye Irritation, Category 2A

Specific Target Organ Systemic Toxicity, Single Exposure, Category 3, Central Nervous System [Inhalation]

Specific Target Organ Systemic Toxicity, Repeated Exposure, Category 2, Blood, Central Nervous System,

Kidneys [Inhalation, Skin absorption, Ingestion]

Aspiration Hazard, Category 1

#### **Physical Hazards**

Flammable Liquid, Category 2

#### **Environmental Hazards**

Chronic Aquatic Toxicity, Category 1

#### **GHS-Labeling**

##### **Pictograms:**





# Safety Data Sheet

REMA TIP TOP

Product #: 517 9008

SDS #: RTT-IND-038

Rev. # 5

Rev. Date: 2/22/2017

**Signal Word: Danger!**

## Hazard Statements

H225: Highly flammable liquid and vapor  
H304: May be fatal if swallowed and enters airways  
H315: Causes skin irritation  
H319: Causes serious eye irritation  
H336: May cause drowsiness or dizziness  
H361: Suspected of damaging fertility or the unborn child  
H373: May cause damage to organs through prolonged or repeated exposure  
H410: Very toxic to aquatic life with long lasting effects

## Precautionary Statements

### Prevention:

P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P233: Keep container tightly closed.  
P235: Keep cool.  
P240: Ground/bond container and receiving equipment.  
P241: Use explosion-proof electrical/ventilating/lighting/equipment.  
P242: Use only non-sparking tools.  
P243: Take precautionary measures against static discharge.  
P260: Do not breathe vapors.  
P264: Wash skin and exposed areas thoroughly after handling.  
P271: Use only outdoors or in a well-ventilated area.  
P273: Avoid release to the environment.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P281: Use personal protective equipment as required.

### Response:

P301 + P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
P302 + P352: IF ON SKIN: Wash with plenty of soap and water.  
P303 + P361 + P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304 + P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313: IF exposed or concerned: Get medical advice/attention.  
P321: Specific treatment found in supplemental First Aid section of this SDS (Section 4).  
P331: Do NOT induce vomiting.  
P332 + P313: If skin irritation occurs: Get medical advice/attention.  
P337 + P313: If eye irritation persists: Get medical advice/attention.  
P370 + P378: In case of fire: Use alcohol-resistant foam, carbon dioxide, or dry chemical for extinction.  
P391: Collect spillage.  
P362: Take off contaminated clothing and wash before reuse.



# Safety Data Sheet

REMA TIP TOP

Product #: 517 9008

SDS #: RTT-IND-038

Rev. # 5

Rev. Date: 2/22/2017

## Storage:

P403 + P233 + P235: Store in a well-ventilated place. Keep container tightly closed. Keep cool.  
P405: Store locked up

## Disposal:

P501: Dispose of contents/container in accordance with local, regional, and federal regulations

### 3. COMPOSITION/ INFORMATION ON INGREDIENTS

#### Chemical characterization

Ester & Aromatic Hydrocarbon Solution

Component*	CAS #	% By Wt.
Ethyl Acetate	141-78-6	55 – 70
Cyclohexane	110-82-7	5 – 15
n-Heptane	142-82-5	2 – 10
Isohexane	107-83-5	2 – 10
n-Hexane	110-54-3	< 2
Zinc Oxide	1314-13-2	< 1

\*The above listed components are OSHA hazardous materials which contribute to this products' GHS Hazard Categorization as prescribed in OSHA's Hazard Communication 29 CFR 1910.1200.

### 4. FIRST AID MEASURES

#### Inhalation

**Symptoms & Effects:** Stomach or intestinal irritation, nausea, vomiting, diarrhea, nose and throat irritation, dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness

**Measures:** Immediately remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing has stopped, begin artificial respiration. If breathing is difficult, administer oxygen. Seek immediate medical attention.

#### Skin Contact

**Symptoms & Effects:** Skin irritation, burning sensation, dry skin, skin cracking, other skin damage

**Measures:** Immediately wash skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes while washing. Wash contaminated clothing before reuse. If skin irritation persists, seek medical attention.

#### Eye Contact

**Symptoms & Effects:** Eye irritation, stinging, tearing, redness, eye swelling



# Safety Data Sheet

REMA TIP TOP

Product #: 517 9008

SDS #: RTT-IND-038

Rev. # 5

Rev. Date: 2/22/2017

**Measures:** Immediately rinse eyes with water for at least 15 minutes. Remove contact lenses after the initial few minutes and if easy to do so and resume rinsing. Rinse beneath eyelids by holding eyelids apart with clean fingers while rinsing. Seek immediate medical attention.

## Ingestion

**Symptoms & Effects:** Stomach or intestinal irritation, nausea, vomiting, diarrhea, nose and throat irritation, dizziness, drowsiness, weakness, fatigue, nausea, headache, and unconsciousness. Since this material is an aspiration hazard, swallowing may result in lung inflammation and other lung injuries.

**Measures:** Seek immediate medical attention. Do NOT induce vomiting. If the victim is drowsy or unconscious, do not give anything by mouth. Do not give milk. Place individual on their left side and place their head down. Do not leave victim unattended.

## 5. FIRE FIGHTING MEASURES

**Suitable Extinguishing Media:** Alcohol-resistant foam, Carbon dioxide, Dry chemical

**Unsuitable Extinguishing Media:** Water stream/jet

**Hazardous Combustion Products:** Carbon monoxide, Carbon dioxide

**Protective Equipment for Fire-Fighters:** Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

**Precautions for Fire-Fighters:** Water stream may be ineffective for extinguishment unless used under favorable conditions. This product is volatile and readily gives off flammable vapors which may travel along the ground or be moved by ventilation. Do not allow run-off from firefighting to enter drains or water courses. Use water spray to cool fully closed containers. Avoid spreading burning liquid with water used for cooling purposes.

## 6. ACCIDENTAL RELEASE MEASURES

**Protective Equipment:** Recommended to wear NIOSH approved respiratory apparatus, chemical splash goggles & resistant gloves and discard of gloves that show tears, pinholes, or signs of wear. Wear proper garments to prevent skin exposure, such as long-sleeves and pants.

**Personal Precautions:** Persons not wearing proper PPE should be excluded from the area of contamination until clean-up has been completed. Ensure adequate ventilation. Eliminate all ignition sources and pay attention to the spreading of gases, especially at ground level.

**Environmental Precautions:** Do not allow discharge into drains, surface waters, or sanitary sewer system. Prevent spreading over a wide area by constructing a dike or using oil barriers. Local authorities should be advised if significant spillages cannot be contained or if material discharges into drains or ground water.



# Safety Data Sheet

## REMA TIP TOP

Product #: 517 9008

SDS #: RTT-IND-038

Rev. # 5

Rev. Date: 2/22/2017

**Methods & Materials for Clean-Up:** Immediately evacuate the spilled area and provide maximum ventilation. Only personnel equipped with proper respiratory, eye, and skin protection should be permitted in the area. Contain spilled material with inert, non-combustible absorbent materials such as sand, earth, diatomaceous earth, or vermiculite. Transfer to a suitable container for disposal according to proper federal, state, and local regulations. Notify the proper response units and agencies for any uncontained releases or spills.

### 7. HANDLING AND STORAGE

**Handling:** Containers of this material may be hazardous when emptied. Since emptied containers still contain product residues (vapor, liquid, or solid), all hazard precautions given in this SDS must be observed. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

Avoid breathing vapors or mists of this product. Avoid eye and skin contact with this material. Skin and eye PPE should be worn at all times when handling this product. When adequate ventilation is not provided, respiratory PPE should also be used. Hands and other exposed areas should be washed thoroughly with soap and water after contact, especially before eating and/or smoking. Do not eat, drink or smoke when using this product.

**Storage:** Store in a cool, dry, ventilated area, away from heat and ignition sources as well as from incompatible materials (see below). Keep container tightly closed and store locked up. Keep away from food, drink, and animal foodstuffs.

**Incompatible Materials:** Strong oxidizing agents, Halogenated compounds, Chlorates, Nitrates, Peroxides, Acids

### 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

#### Exposure Limits :

Exposure limits have not been established for this product.

#### **Ethyl Acetate CAS # 141-78-6**

OSHA	Permissible Exposure Limit (PEL)	400 ppm (1,400 mg/m <sup>3</sup> )
ACGIH	Time Weighted Average (TWA)	400 ppm (1,400 mg/m <sup>3</sup> )
NIOSH	Recommended Exposure Limit (REL)	400 ppm (1,400 mg/m <sup>3</sup> )

#### **Cyclohexane CAS # 110-82-7**

OSHA	Permissible Exposure Limit (PEL)	300 ppm (1,050 mg/m <sup>3</sup> )
ACGIH	Time Weighted Average (TWA)	100 ppm
NIOSH	Recommended Exposure Limit (REL)	300 ppm (1,050 mg/m <sup>3</sup> )



# Safety Data Sheet

## REMA TIP TOP

Product #: 517 9008

SDS #: RTT-IND-038

Rev. # 5

Rev. Date: 2/22/2017

<b>n-Heptane</b>	<b>CAS # 142-82-5</b>	
OSHA	Permissible Exposure Limit (PEL)	500 ppm (2,000 mg/m <sup>3</sup> )
ACGIH	Time Weighted Average (TWA)/(STEL)	400 ppm/500 ppm
NIOSH	Recommended Exposure Limit (REL)	85 ppm (350 mg/m <sup>3</sup> )
<b>Isohexane</b>	<b>CAS # 107-83-5</b>	
ACGIH	Time Weighted Average (TWA)/(STEL)	500 ppm/1000 ppm
<b>n-Hexane</b>	<b>CAS # 110-54-3</b>	
OSHA	Permissible Exposure Limit (PEL)	500 ppm (1,800 mg/m <sup>3</sup> )
ACGIH	Time Weighted Average (TWA)	50 ppm (176 mg/m <sup>3</sup> )
NIOSH	Recommended Exposure Limit (REL)	50 ppm (176 mg/m <sup>3</sup> )
<b>Zinc Oxide</b>	<b>CAS # 1314-13-2</b>	
OSHA	Permissible Exposure Limit (PEL)	5 mg/m <sup>3</sup>
ACGIH	Time Weighted Average (TWA)/(STEL)	2 mg/m <sup>3</sup> /10 mg/m <sup>3</sup>
NIOSH	Recommended Exposure Limit (REL)	5 mg/m <sup>3</sup>

**Engineering Controls:** Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposures below permissible exposure limits. Provide readily accessible eye wash stations and safety showers.

**Occupational Exposure Controls:** Ensure adequate ventilation, especially in confined areas. Consider all potential hazards of this material, applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting PPE. Ensure that eyewash stations and safety showers are proximal to the work location. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

**Protective and Hygiene measures:** Do not inhale vapors. Wash hands before breaks and immediately after handling product. When using, do not eat, drink, or smoke. In case of clothes contamination, remove and wash contaminated clothing before re-use.

**Eye Protection:** Recommended to wear tight fitting, chemical splash goggles when there is potential for the exposure of the eyes to the liquid, vapor or mist. Have a suitable eye wash station or bottle nearby in case of splashing into the eyes.

**Hand Protection:** Recommended to wear suitable resistant gloves and discard of gloves that show tears, pinholes, or signs of wear. Suitable gloves will be based on product use and the period of use, and may include neoprene, butyl-rubber, nitrile rubber, etc.

**Skin Protection:** Recommended to wear impervious clothing as well as long-sleeved clothing, pants and proper foot covering in order to prevent direct skin contact with the product. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.



# Safety Data Sheet

REMA TIP TOP

Product #: 517 9008

SDS #: RTT-IND-038

Rev. # 5

Rev. Date: 2/22/2017

**Respiratory Protection:** A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be appropriate where airborne concentrations are expected to exceed exposure limits or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** Black liquid

**Odor:** Ester-like

**Odor Threshold:** No data available

**pH:** No data available

**Melting/Freezing point:** < - 4°F (< - 20°C)

**Boiling Point/ Range:** 169°F (76°C)

**Flash point (Tag closed cup):** < -0.4°F (< -18°C)

**Evaporation rate:** > 1.0 n-Butyl Acetate

**Flammability: Lower Limit:** 0.6% (V) **Upper Limit:** 11.5% (V)

**Vapor pressure:** No data available

**Relative vapor density:** 3.0 (Air = 1)

**Density:** 0.90 g/cm<sup>3</sup> (7.5 lbs/gal) @ 68°F (20°C)

**Solubility in water:** Immiscible

**Partition coefficient (n-octanol/water):** No data available

**Auto-ignition temperature:** > 430°F (> 220°C)

**Ignition temperature:** 860°F (460°C)

**Decomposition temperature:** No data available

**Viscosity (dynamic):** No data available

## 10. STABILITY AND REACTIVITY

**Reactivity:** No decomposition if stored and applied as directed.

**Chemical Stability:** Stable under normal conditions.

**Possibility of Hazardous Reactions:** Product will not undergo hazardous polymerization or other hazardous reactions if storage and use directions are followed.

**Conditions to Avoid:** Elevated temperatures, Ignition sources, Incompatible materials (see below)

**Incompatible Materials:** Strong oxidizing agents, Halogenated compounds, Chlorates, Nitrates, Peroxides, Acids

**Hazardous decomposition products:** Carbon monoxide, Carbon dioxide





# Safety Data Sheet

REMA TIP TOP

Product #: 517 9008

SDS #: RTT-IND-038

Rev. # 5

Rev. Date: 2/22/2017

## 11. TOXICOLOGICAL INFORMATION

**Primary Routes of Exposure:** Inhalation, Skin contact, Eye contact, Ingestion

**Symptoms Related to Physical, Chemical and Toxicological Characteristics:** Stomach or intestinal irritation, nausea, vomiting, diarrhea, nose and throat irritation, dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness, skin irritation, burning sensation, dry skin, skin cracking, other skin damage, eye irritation, stinging, tearing, redness, and eye swelling. Since this material is an aspiration hazard, swallowing may result in lung inflammation and other lung injuries.

**Delayed and Immediate Effects & Chronic Effects from Exposure:** This substance may lead to central nervous system depression and effects such as drowsiness or dizziness. This substance is suspected of harming fertility or causing damage to the unborn child. With repeated exposure, the substance may have toxic effects on the blood, central nervous system and kidneys.

### Measures of Toxicity:

Acute toxicities are calculated based on component toxicities

Mixture: Acute Oral Toxicity: LD<sub>50</sub> Rat: > 5,000 mg/kg

Acute Dermal Toxicity: LD<sub>50</sub> Rabbit: > 2,000 mg/kg

Acute Inhalation Toxicity: LC<sub>50</sub> Rat: > 20,000 ppmV

### Ethyl Acetate

CAS # 141-78-6

Acute Oral Toxicity

LD<sub>50</sub> Rat: 5,620 mg/kg

Acute Dermal Toxicity

LD<sub>50</sub> Rabbit: > 180,000 mg/kg

Acute Inhalation Toxicity

LC<sub>50</sub> Rat: 16,000 mg/l (6 h)

### Cyclohexane

CAS # 110-82-7

Acute Oral Toxicity

LD<sub>50</sub> Rat: > 5,000 mg/kg

Acute Dermal Toxicity

LD<sub>50</sub> Rabbit: > 2,000 mg/kg

Acute Inhalation Toxicity

LC<sub>50</sub> Rat: > 32,880 mg/m<sup>3</sup>

### n-Heptane

CAS # 142-82-5

Acute Oral Toxicity

LD<sub>50</sub> Rat: > 5,000 mg/kg

Acute Dermal Toxicity

LD<sub>50</sub> Rabbit: > 2,000 mg/kg

Acute Inhalation Toxicity

LC<sub>50</sub> Rat: 103,000 mg/m<sup>3</sup>

### n-Hexane

CAS # 110-54-3

Acute Oral Toxicity

LD<sub>50</sub> Rat: 25,000 mg/kg

Acute Inhalation Toxicity

LC<sub>50</sub> Rat: 48,000 ppmV

### Zinc Oxide

CAS # 1314-13-2

Acute Oral Toxicity

LD<sub>50</sub> Mouse: 7,950 mg/kg

Acute Inhalation Toxicity

LC<sub>50</sub> Mouse: 2,500 mg/m<sup>3</sup>





# Safety Data Sheet

REMA TIP TOP

Product #: 517 9008

SDS #: RTT-IND-038

Rev. # 5

Rev. Date: 2/22/2017

## Carcinogen Claims:

OSHA: **None**, International Agency for Research on Cancer (IARC): **None**

ACGIH: **None**, National Toxicology Program (NTP) Report on Carcinogens: **None**

## 12. ECOLOGICAL INFORMATION

**Eco-toxicity:** This substance is very toxic to aquatic organisms with long lasting effects. It is strongly advised that this substance does not enter the environment. Local authorities should be immediately advised if significant spillages cannot be contained or if material discharges into drains or ground water.

**Ethyl Acetate**            **CAS # 141-78-6**  
Toxicity to Fish     $LC_{50}$  – 220 mg/l (Fathead Minnow; 96 h)  
Toxicity to Fish     $LC_{50}$  – 350 mg/l (Rainbow Trout; 96 h)  
Toxicity to Daphnia  $LC_{50}$  – 154 mg/l (Water Flea; 48 h)  
Toxicity to Algae     $EC_{50}$  – 4,300 mg/l (Algae; 24 h)

**Cyclohexane**            **CAS # 110-82-7**  
Toxicity to Fish     $LC_{50}$  – 4.53 mg/l (Fathead Minnow; 96 h)  
Toxicity to Daphnia  $EC_{50}$  – 0.9 mg/l (Water Flea; 48 h)  
Toxicity to Algae     $EC_{50}$  – 3.4 mg/l (Algae; 72 h)

**Zinc Oxide**            **CAS # 1314-13-2**  
Toxicity to Fish     $LC_{50}$  – 1.1 mg/l (Rainbow Trout; 96 h)  
Toxicity to Daphnia  $EC_{50}$  – 0.098 mg/l (Water Flea; 48 h)

**Persistence & Degradability:** No data available

**Bio-accumulative Potential:** No data available

**Mobility in Soil:** No data available

**Other Adverse Effects:** No data available

## 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with Federal, State or Local regulations.  
Contaminated packaging should be emptied as far as possible before disposal.



# Safety Data Sheet

REMA TIP TOP

Product #: 517 9008

SDS #: RTT-IND-038

Rev. # 5

Rev. Date: 2/22/2017

---

## 14. TRANSPORT INFORMATION

### DOT SHIPPING CLASSIFICATION:

UN NUMBER: UN1133

PROPER SHIPPING NAME: Adhesives, containing a flammable liquid (Ethyl Acetate, Cyclohexane, n-Heptane)

TRANSPORTATION HAZARD CLASS: 3

PACKING GROUP: II

HAZARD LABEL: 3

### IMDG (Marine) SHIPPING CLASSIFICATION:

IMDG CODE: 3

UN NUMBER: UN1133

MARINE POLLUTANT: Yes

EmS: F-E, S-D

IMDG PACKING GROUP: II

HAZARD LABEL: 3

### Description of the goods

ADHESIVES, CONTAINING A FLAMMABLE LIQUID (ETHYL ACETATE, CYCLOHEXANE, N-HEPTANE)

### IATA (Air) SHIPPING CLASSIFICATION:

ICAO/IATA-DGR: 3

UN NUMBER: UN1133

HAZARD LABEL: 3

### Description of the goods

Adhesives, containing a flammable liquid (Ethyl Acetate, Cyclohexane, n-Heptane)

## 15. REGULATORY INFORMATION

All components of this product conform to the following national inventory requirements. US TSCA, EU EINECS and Canada DSL

### SARA Title III

#### Section 302 – Extremely Hazardous Chemicals

The following ingredients are subject to the supplier notification requirements of Section 302 of the Superfund Amendments and Reauthorization Act (SARA/EPCRA) and the requirements of 40 CFR Part 37 *None Listed*



# Safety Data Sheet

REMA TIP TOP

Product #: 517 9008

SDS #: RTT-IND-038

Rev. # 5

Rev. Date: 2/22/2017

## Section 313 – Toxic Chemicals

The following ingredients are subject to the supplier notification requirements of Section 313 of the Superfund Amendments and Reauthorization Act (SARA/EPCRA) and the requirements of 40 CFR Part 37

Component	CAS #	Weight %	CERCLA RQ
Ethyl Acetate	141-78-6	55 – 70	5,000
Cyclohexane	110-82-7	5 – 15	1,000
n-Hexane	110-54-3	< 2	5,000

## OTHER FEDERAL REGULATIONS

Components of this product are subject to RCRA Hazardous Waste requirements. Clean Air Act (CAA) Hazardous Air Pollutants requirements and OSHA Process Safety Management (PSM) high hazard requirements.

## CANADIAN REGULATIONS

WHMIS Classification: Same as OSHA GHS Classification.

## STATE REGULATIONS

### California Proposition 65

This product does not contain chemicals known to the state of California to cause cancer, birth defects or reproductive harm.

California Hazardous Substances List/Permissible Exposure List

California Toxic air contaminants

Connecticut Permissible Exposure Limits

Delaware List of Chemicals and RQs

Hawaii Permissible Exposure Limits

Idaho Toxic Air Pollutants

Illinois Toxic Air Contaminants List

Louisiana Toxic Air Pollutants

Maine Hazardous Air Pollutants

Maryland Toxic Air Pollutants for Existing Sources

Massachusetts Hazardous Substances List

Michigan Permissible Exposure Limits

Minnesota Hazardous Substances

Minnesota Permissible Exposure Limits

Nebraska Hazardous Air Pollutants

New Jersey RTK Hazardous Substances List/TCPA Extremely Hazardous Substances List

New York List of Hazardous Substances

Ohio Toxic Air Contaminants

Oklahoma Toxic Air Contaminants

North Carolina TAP Emissions Rates Requiring a Permit

Pennsylvania Hazardous Substances List



# Safety Data Sheet

REMA TIP TOP

Product #: 517 9008

SDS #: RTT-IND-038

Rev. # 5

Rev. Date: 2/22/2017

Rhode Island Toxic Air Contaminants  
Tennessee Permissible Exposure Limits  
Vermont Hazardous Air Contaminants/Permissible Exposure Limits  
Washington Permissible Exposure Limits for Airborne Contaminants.  
West Virginia Toxic Air Pollutant List  
Wisconsin hazardous Air Contaminants

**Note:** Entries under Section 15 are not intended to be all inclusive of Federal and State laws and regulations. Please consult the appropriate agencies for further clarification of any requirements.

## 16. OTHER INFORMATION

This SDS conforms to the OSHA Hazard Communication Standard 1910.1200 published in the Federal Register March 26, 2012

**MEDICAL EMERGENCIES:**

Call CHEMTREC 24 hours a  
Day for emergency information  
800-424-9300

**FOR ANY OTHER INFORMATION:**

REMA TIP TOP - NORTH AMERICA  
119 Rockland Ave.  
NORTHVALE, NJ 07647  
201-256-8200

**NOTICE:** REMA TIP TOP NORTH AMERICA believes that the information contained on this safety data sheet is accurate. The suggested procedures are based on experience as of the date of publication. They are not necessarily all-inclusive, nor fully adequate in every circumstance. Also, the suggestions should not be confused with, nor followed in violation of, applicable laws, regulations, rules or insurance requirements.

**NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE.**