



# Safety Data Sheet

## REMA TIP TOP

Product #s: 5252303, 5252327, 5252334

SDS #: RTT-IND-106

Rev. # 4

Rev. Date: 6/292017

---

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** Tip Top Metal Primer PR 500-1

**Chemical Family:** Ketone & Aromatic Hydrocarbon Solution

**Product Use:** Primer coating

**Restrictions on Use:** Use as directed by manufacturer

**Distributed By:** Rema Tip Top - North America  
240 Pegasus Avenue, 2<sup>nd</sup> floor.  
Northvale, NJ 07647  
Phone: 201 256-8200

**24-Hour Emergency Phone Number:** North America: 800-424-9300 (CHEMTREC)  
International: 703-527-3887 (CHEMTREC) Collect Calls Accepted

### 2. HAZARD IDENTIFICATION

#### GHS Classifications

##### **Health Hazards**

Acute Toxicity, Inhalation, Category 4  
Skin Irritation, Category 2  
Eye Irritation, Category 2A  
Skin Sensitizer, Category 1q  
Germ Cell Mutagenicity, Category 2  
Carcinogenicity, Category 2  
Reproductive Toxicity, Category 2  
Specific Target Organ Systemic Toxicity, Single Exposure, Category 3, Respiratory Tract [Inhalation]  
Specific Target Organ Systemic Toxicity, Repeated Exposure, Category 2, Central Nervous System, Blood, Kidneys, Liver, Pancreas, Spleen [Inhalation, Skin absorption, Ingestion]

##### **Physical Hazards**

Flammable Liquid, Category 2

##### **Environmental Hazards**

Chronic Aquatic Toxicity, Category 2

##### **GHS-Labeling**

##### **Pictograms:**



# Safety Data Sheet

## REMA TIP TOP

Product #s: 5252303, 5252327, 5252334

SDS #: RTT-IND-106

Rev. # 4

Rev. Date: 6/292017



**Signal Word: Danger!**

### Hazard Statements

H225: Highly flammable liquid and vapor  
H303: Can be harmful if swallowed  
H315: Causes skin irritation  
H319: Causes serious eye irritation  
H332: Harmful if inhaled  
H335: May cause respiratory irritation  
H341: Suspected of causing genetic defects  
H351: Suspected of causing cancer  
H361: Suspected of damaging fertility or the unborn child  
H373: May cause damage to organs through prolonged or repeated exposure  
H411: Toxic to aquatic life with long lasting effects

### Precautionary Statements

#### Prevention:

P202: Do not handle until all safety precautions have been read and understood.  
P210: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.  
P233: Keep container tightly closed.  
P235: Keep cool.  
P240: Ground/bond container and receiving equipment.  
P241: Use explosion-proof electrical/ventilating/lighting/equipment.  
P242: Use only non-sparking tools.  
P243: Take precautionary measures against static discharge.  
P260: Do not breathe vapours.  
P264: Wash skin and exposed areas thoroughly after handling.  
P271: Use only outdoors or in a well-ventilated area.  
P273: Avoid release to the environment.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P281: Use personal protective equipment as required.  
P285: In case of inadequate ventilation, wear respiratory protection.

#### Response:

P302 + P352: IF ON SKIN: Wash with plenty of soap and water.  
P303 + P361 + P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304 + P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.



# Safety Data Sheet

## REMA TIP TOP

Product #s: 5252303, 5252327, 5252334

SDS #: RTT-IND-106

Rev. # 4

Rev. Date: 6/292017

P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313: IF exposed or concerned: Get medical/advice attention.  
P314: Get medical advice/attention if you feel unwell.  
P321: Specific treatment found in supplemental First Aid section of this SDS (Section 4).  
P332 + P313: If skin irritation occurs: Get medical advice/attention.  
P337 + P313: If eye irritation persists: Get medical advice/attention.  
P370 + P378: In case of fire: Use alcohol-resistant foam, carbon dioxide, or dry chemical for extinction.  
P362: Take off contaminated clothing and wash before reuse.  
P391: Collect spillage.

### Storage:

P403 + P233 + P235: Store in a well-ventilated place. Keep container tightly closed. Keep cool.  
P405: Store locked up

### Disposal:

P501: Dispose of contents/container in accordance with local, regional, and federal regulations

## 3. COMPOSITION/ INFORMATION ON INGREDIENTS

### Chemical characterization

Ketone & Aromatic Hydrocarbon Solution

Component*	CAS #	% By Wt.
Methyl Isobutyl Ketone (MIBK)	108-10-1	>60
Xylene	1330-20-7	5 - 10
Ethyl Benzene	100-41-4	1 - 5
Phenol Resin	9003-35-4	1 - 5
Phenol	108-95-2	< 3
Zinc Oxide	1314-13-2	< 2.5
Toluene	108-88-3	< 1

\*The above listed components are OSHA hazardous materials which contribute to this products' GHS Hazard Categorization as prescribed in OSHA's Hazard Communication 29 CFR 1910.1200.

## 4. FIRST AID MEASURES

### Inhalation

**Symptoms & Effects:** Nausea, nose and throat irritation, respiratory tract irritation, dizziness, drowsiness, headache, confusion, shortness of breath



# Safety Data Sheet

## REMA TIP TOP

Product #s: 5252303, 5252327, 5252334

SDS #: RTT-IND-106

Rev. # 4

Rev. Date: 6/292017

**Measures:** Immediately remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing has stopped, begin artificial respiration. If breathing is difficult, administer oxygen. Seek immediate medical attention.

### Skin Contact

**Symptoms & Effects:** Skin irritation, redness, skin drying

**Measures:** Wash skin with plenty of water. Remove contaminated clothing and shoes while washing. Wash contaminated clothing before reuse. If skin irritation develops, seek medical attention.

### Eye Contact

**Symptoms & Effects:** Eye irritation, stinging, tearing, redness, eye swelling

**Measures:** Immediately rinse eyes with water for at least 15 minutes. Remove contact lenses after the initial few minutes and if easy to do so and resume rinsing. Rinse beneath eyelids by holding eyelids apart with clean fingers while rinsing. Seek immediate medical attention.

### Ingestion

**Symptoms & Effects:** Stomach or intestinal irritation, nausea, vomiting, diarrhea, dizziness, drowsiness

**Measures:** Seek immediate medical attention. Do NOT induce vomiting unless directed to do so by a physician or medical personnel. If the victim is drowsy or unconscious, do not give anything by mouth. Do not give milk. Place individual on their left side and place their head down. Do not leave victim unattended.

## 5. FIRE FIGHTING MEASURES

**Suitable Extinguishing Media:** Alcohol-resistant foam, Carbon dioxide, Dry chemical, Water spray

**Unsuitable Extinguishing Media:** Water stream/jet

**Hazardous Combustion Products:** Hydrogen chloride, Formaldehyde, Carbon monoxide, Carbon dioxide

**Protective Equipment for Fire-Fighters:** Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

**Precautions for Fire-Fighters:** This product and the vapors it produces are highly flammable. Vapors are heavier than air and spread along the ground. The vapor/air mixture is explosive, even in empty, un-cleaned containers. Water stream may be ineffective for extinguishment unless used under favorable conditions. This product is volatile and readily gives off flammable vapors which may travel along the ground or be moved by ventilation. Do not allow run-off from firefighting to enter drains or water courses. Use water spray to cool fully closed containers. Avoid spreading burning liquid with water used for cooling purposes.



# Safety Data Sheet

## REMA TIP TOP

Product #s: 5252303, 5252327, 5252334

SDS #: RTT-IND-106

Rev. # 4

Rev. Date: 6/292017

### 6. ACCIDENTAL RELEASE MEASURES

**Protective Equipment:** Recommended to wear NIOSH approved respiratory apparatus, chemical splash goggles & resistant gloves and discard of gloves that show tears, pinholes, or signs of wear. Wear proper garments to prevent skin exposure, such as long-sleeves and pants.

**Personal Precautions:** Persons not wearing proper PPE should be excluded from the area of contamination until clean-up has been completed. Ensure adequate ventilation. Eliminate all ignition sources and pay attention to the spreading of gases, especially at ground level.

**Environmental Precautions:** Do not allow discharge into drains, surface waters, or sanitary sewer system. Prevent spreading over a wide area by constructing a dike or using oil barriers. Local authorities should be advised if significant spillages cannot be contained or if material discharges into drains or ground water.

**Methods & Materials for Clean-Up:** Immediately evacuate the spilled area and provide maximum ventilation. Only personnel equipped with proper respiratory, eye, and skin protection should be permitted in the area. Contain spilled material with inert, non-combustible absorbent materials such as sand, earth, diatomaceous earth, or vermiculite. Transfer to a suitable container for disposal according to proper federal, state, and local regulations. Notify the proper response units and agencies for any uncontained releases or spills.

### 7. HANDLING AND STORAGE

**Handling:** Containers of this material may be hazardous when emptied. Since emptied containers still contain product residues (vapor, liquid, or solid), all hazard precautions given in this SDS must be observed. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

Avoid breathing vapors or mists of this product. Avoid eye and skin contact with this material. Skin and eye PPE should be worn at all times when handling this product. When adequate ventilation is not provided, respiratory PPE should also be used. Hands and other exposed areas should be washed thoroughly with soap and water after contact, especially before eating and/or smoking. Do not eat, drink or smoke when using this product.

**Storage:** Store in a cool, dry, ventilated area, away from heat and ignition sources as well as from incompatible materials (see below). Keep container tightly closed and store locked up. Keep away from food, drink, and animal foodstuffs.

**Incompatible Materials:** Oxidizing agents, Strong bases, Strong acids



# Safety Data Sheet

## REMA TIP TOP

Product #s: 5252303, 5252327, 5252334

SDS #: RTT-IND-106

Rev. # 4

Rev. Date: 6/292017

### 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

#### Exposure Limits :

Exposure limits have not been established for this product.

#### Methyl Isobutyl

##### **Ketone (MIBK) CAS # 108-10-1**

OSHA	Permissible Exposure Limit (PEL)	100 ppm (410 mg/m <sup>3</sup> )
ACGIH	Time Weighted Average (TWA)	20 ppm (75 mg/m <sup>3</sup> )
NIOSH	Recommended Exposure Limit (REL)	50 ppm (205 mg/m <sup>3</sup> )

#### Xylene

##### **CAS # 1330-20-7**

OSHA	Permissible Exposure Limit (PEL)	100 ppm (435 mg/m <sup>3</sup> )
ACGIH	Time weighted average (TWA)	100 ppm (434 mg/m <sup>3</sup> )
NIOSH	Recommended Exposure Limit (REL)	100 ppm (435 mg/m <sup>3</sup> )

#### Phenol

##### **CAS # 108-95-2**

OSHA	Permissible Exposure Limit (PEL)	5 ppm (19 mg/m <sup>3</sup> )
ACGIH	Time Weighted Average (TWA)	5 ppm (19 mg/m <sup>3</sup> )
NIOSH	Recommended Exposure Limit (REL)	5 ppm (19 mg/m <sup>3</sup> )

#### Zinc Oxide

##### **CAS # 1314-13-2**

OSHA	Permissible Exposure Limit (PEL)	5 mg/m <sup>3</sup>
ACGIH	Time Weighted Average (TWA)	2 mg/m <sup>3</sup>
NIOSH	Recommended Exposure Limit (REL)	5 mg/m <sup>3</sup>

#### Toluene

##### **CAS # 108-88-3**

OSHA	Permissible Exposure Limit (PEL)	200 ppm (750 mg/m <sup>3</sup> )
ACGIH	Time Weighted Average (TWA)	20 ppm (75 mg/m <sup>3</sup> )
NIOSH	Recommended Exposure Limit (REL)	100 ppm (375 mg/m <sup>3</sup> )

**Engineering Controls:** Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposures below permissible exposure limits. Provide readily accessible eye wash stations and safety showers.

**Occupational Exposure Controls:** Ensure adequate ventilation, especially in confined areas. Consider all potential hazards of this material, applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting PPE. Ensure that eyewash stations and safety showers are proximal to the work location. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

**Protective and Hygiene measures:** Do not inhale vapors. Wash hands before breaks and immediately after handling product. When using, do not eat, drink, or smoke. In case of clothes contamination, remove and wash contaminated clothing before re-use.



# Safety Data Sheet

## REMA TIP TOP

Product #s: 5252303, 5252327, 5252334

SDS #: RTT-IND-106

Rev. # 4

Rev. Date: 6/292017

**Eye Protection:** Recommended to wear tight fitting, chemical splash goggles when there is potential for the exposure of the eyes to the liquid, vapor or mist. Have a suitable eye wash station or bottle nearby in case of splashing into the eyes.

**Hand Protection:** Recommended to wear suitable resistant gloves and discard of gloves that show tears, pinholes, or signs of wear. Suitable gloves will be based on product use and the period of use, and may include neoprene, butyl-rubber, nitrile rubber, etc.

**Skin Protection:** Recommended to wear impervious clothing as well as long-sleeved clothing, pants and proper foot covering in order to prevent direct skin contact with the product. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.

**Respiratory Protection:** A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be appropriate under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** Grey Liquid

**Odor:** Aromatic Solvent

**Odor Threshold:** No data available

**pH:** No data available

**Melting/Freezing point:** < -58°F (< -50°C)

**Boiling Point/ Range:** 243°F (117°C)

**Flash point (Tag closed cup):** 59°F (15°C)

**Evaporation rate:** No data available

**Flammability: Lower Limit:** 1.4% (V) **Upper Limit:** 7.5% (V)

**Vapor pressure:** No data available

**Relative vapor density:** > 3 (Air = 1)

**Density:** 0.96 g/cm<sup>3</sup> (8.0 lbs/gal) @ 68°F (20°C)

**Solubility in water:** Insoluble

**Partition coefficient (n-octanol/water):** No data available

**Auto-ignition temperature:** 842°F (450°C)

**Ignition temperature:** No data available

**Decomposition temperature:** No data available

**Viscosity (dynamic):** No data available





# Safety Data Sheet

## REMA TIP TOP

Product #s: 5252303, 5252327, 5252334

SDS #: RTT-IND-106

Rev. # 4

Rev. Date: 6/292017

### 10. STABILITY AND REACTIVITY

**Reactivity:** No decomposition if stored and applied as directed.

**Chemical Stability:** Stable under normal conditions.

**Possibility of Hazardous Reactions:** Product will not undergo hazardous polymerization or other hazardous reactions if storage and use directions are followed.

**Conditions to Avoid:** Elevated temperatures, Ignition sources, Incompatible materials (see below)

**Incompatible Materials:** Oxidizing agents, Strong bases, Strong acids

**Hazardous decomposition products:** Hydrogen chloride, Formaldehyde, Carbon monoxide, Carbon dioxide

### 11. TOXICOLOGICAL INFORMATION

**Primary Routes of Exposure:** Inhalation, Skin contact, Eye contact, Ingestion

**Symptoms Related to Physical, Chemical and Toxicological Characteristics:** Nausea, nose and throat irritation, respiratory tract irritation, dizziness, drowsiness, headache, confusion, shortness of breath, skin irritation, redness, skin drying, eye irritation, stinging, tearing, redness, eye swelling, stomach or intestinal irritation, vomiting, diarrhea

**Delayed and Immediate Effects & Chronic Effects from Exposure:** This substance may result in respiratory irritation. With repeated exposure, the substance may have toxic effects on the central nervous system, blood, kidneys, liver, pancreas, and spleen. This substance is suspected to cause mutagenic effects based on studies of laboratory animals alone. This substance is suspected of harming fertility or the unborn child based on studies of laboratory animals alone. This substance is a suspected carcinogen as outlined by OSHA and the IARC.

#### **Measures of Toxicity:**

Acute toxicities are calculated based on component toxicities

Mixture: Acute Oral Toxicity: LD<sub>50</sub> Rat: > 2,400 mg/kg

Acute Dermal Toxicity: LD<sub>50</sub> Rabbit: > 22,000 mg/kg

Acute Inhalation Toxicity: No sufficient data available

#### **Methyl Isobutyl Ketone (MIBK)**

**CAS # 108-10-1**

Acute Oral Toxicity

LD<sub>50</sub> Rat: 2,080 mg/kg

Acute Dermal Toxicity

LD<sub>50</sub> Rabbit: > 26,000 mg/kg

#### **Xylene**

**CAS # 1330-20-7**

Acute Oral Toxicity

LD<sub>50</sub> Rat: 4,300 mg/kg

Acute Dermal Toxicity

LD<sub>50</sub> Rabbit: > 1,700 mg/kg

Acute Inhalation Toxicity

LC<sub>50</sub> Rat: 5,000 ppm





# Safety Data Sheet

## REMA TIP TOP

Product #s: 5252303, 5252327, 5252334

SDS #: RTT-IND-106

Rev. # 4

Rev. Date: 6/292017

**Phenol** CAS # 108-95-2  
Acute Oral Toxicity LD<sub>50</sub> Rat: 317 mg/kg  
Acute Dermal Toxicity LD<sub>50</sub> Rabbit: 630 mg/kg  
Acute Inhalation Toxicity LC<sub>50</sub> Rat: 900 mg/m<sup>3</sup> (8 h)

**Zinc Oxide** CAS # 1314-13-2  
Acute Oral Toxicity LD<sub>50</sub> Mouse: 7,950 mg/kg  
Acute Inhalation Toxicity LC<sub>50</sub> Mouse: 2,500 mg/m<sup>3</sup>

**Toluene** CAS # 108-88-3  
Acute Oral Toxicity LD<sub>50</sub> Rat: > 5,580 mg/kg  
Acute Inhalation Toxicity LC<sub>50</sub> Rat: 12,500 mg/m<sup>3</sup> (6 h)

### Carcinogen Claims:

OSHA: **Yes; 2**, International Agency for Research on Cancer (IARC): **Yes; 2B [Possibly Carcinogenic to Humans]**, ACGIH: **No; A3 [Animal Carcinogen, not likely in Humans]**  
National Toxicology Program (NTP) Report on Carcinogens: **None**

## 12. ECOLOGICAL INFORMATION

**Eco-toxicity:** This substance is toxic to aquatic life with long lasting effects. It is still strongly advised that this substance does not enter the environment. Local authorities should be advised if significant spillages cannot be contained or if material discharges into drains or ground water.

**Xylene** CAS # 1330-20-7  
Toxicity to Fish LC<sub>50</sub> – 19.2 mg/l (Fathead Minnow; 96 h)  
Toxicity to Daphnia EC<sub>50</sub> – 1.37 mg/l (Water flea; 48 h)

**Phenol** CAS # 108-95-2  
Toxicity to Fish LC<sub>50</sub> – 14 mg/l (Golden Orfe; 48 h)  
Toxicity to Fish LC<sub>50</sub> – 36.1 mg/l (Goldfish; 96 h)  
Toxicity to Daphnia EC<sub>50</sub> – 12 mg/l (Water Flea; 24 h)  
Toxicity to Algae EC<sub>50</sub> – 370 mg/l (Fresh Water Algae; 96 h)

**Zinc Oxide** CAS # 1314-13-2  
Toxicity to Fish LC<sub>50</sub> – 1.1 mg/l (Rainbow Trout; 96 h)  
Toxicity to Daphnia EC<sub>50</sub> – 0.098 mg/l (Water Flea; 48 h)

**Toluene** CAS # 108-88-3  
Toxicity to Fish LC<sub>50</sub> – 7.63 mg/l (Rainbow Trout; 96 h)  
Toxicity to Fish LC<sub>50</sub> – 8.04 mg/l (Fathead Minnow; 96 h)  
Toxicity to Fish LC<sub>50</sub> – 74 mg/l (Bluegill; 96 h)  
Toxicity to Daphnia EC<sub>50</sub> – 8.0 mg/l (Water Flea; 48 h)



# Safety Data Sheet

## REMA TIP TOP

Product #s: 5252303, 5252327, 5252334

SDS #: RTT-IND-106

Rev. # 4

Rev. Date: 6/292017

**Persistence & Degradability:** No data available

**Bio-accumulative Potential:** No data available

**Mobility in Soil:** No data available

**Other Adverse Effects:** No data available

### 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with Federal, State or Local regulations.  
Contaminated packaging should be emptied as far as possible before disposal.

### 14. TRANSPORT INFORMATION

#### **DOT SHIPPING CLASSIFICATION:**

UN NUMBER: UN1133

PROPER SHIPPING NAME: Adhesives, containing a flammable liquid (Methyl Isobutyl Ketone, Xylene)

TRANSPORTATION HAZARD CLASS: 3

PACKING GROUP: II

HAZARD LABEL: 3

#### **IMDG (Marine) SHIPPING CLASSIFICATION:**

IMDG CODE: 3

UN NUMBER: UN1133

MARINE POLLUTANT: Yes

EmS: F-E, S-D

IMDG PACKING GROUP: II

HAZARD LABEL: 3

#### **Description of the goods**

ADHESIVES, CONTAINING A FLAMMABLE LIQUID (METHYL ISOBUTYL KETONE, XYLENE)

#### **IATA (Air) SHIPPING CLASSIFICATION:**

ICAO/IATA-DGR: 3

UN NUMBER: UN1133

HAZARD LABEL: 3

#### **Description of the goods**

Adhesives, containing a flammable liquid (Methyl Isobutyl Ketone, Xylene)

### 15. REGULATORY INFORMATION

All components of this product conform to the following national inventory requirements. US TSCA, EU EINECS and Canada DSL



# Safety Data Sheet

## REMA TIP TOP

Product #s: 5252303, 5252327, 5252334

SDS #: RTT-IND-106

Rev. # 4

Rev. Date: 6/292017

### SARA Title III

#### Section 302 – Extremely Hazardous Chemicals

The following ingredients are subject to the supplier notification requirements of Section 302 of the Superfund Amendments and Reauthorization Act (SARA/EPCRA) and the requirements of 40 CFR Part 37

Component	CAS #	Weight %	CERCLA RQ
Phenol	108-95-2	< 3	1,000

#### Section 313 – Toxic Chemicals

The following ingredients are subject to the supplier notification requirements of Section 313 of the Superfund Amendments and Reauthorization Act (SARA/EPCRA) and the requirements of 40 CFR Part 37

Component	CAS #	Weight %	CERCLA RQ
Methyl Isobutyl Ketone	108-10-1	60 – 75	5,000
Xylene	1330-20-7	15 – 30	100
Phenol	108-95-2	< 3	1,000
Toluene	108-88-3	< 1	1,000

### OTHER FEDERAL REGULATIONS

Components of this product are subject to RCRA Hazardous Waste requirements.  
Clean Air Act (CAA) Hazardous Air Pollutants requirements and OSHA Process Safety Management (PSM) high hazard requirements.

### CANADIAN REGULATIONS

Same as OSHA GHS Classification

### STATE REGULATIONS

#### California Proposition 65

**WARNING!** This product contains a chemical known to the state of California to cause cancer and reproductive toxicity.

California Hazardous Substances List/Permissible Exposure List

California Toxic air contaminants

Connecticut Permissible Exposure Limits

Delaware List of Chemicals and RQs

Hawaii Permissible Exposure Limits

Idaho Toxic Air Pollutants

Illinois Toxic Air Contaminants List

Louisiana Toxic Air Pollutants

Maine Hazardous Air Pollutants

Maryland Toxic Air Pollutants for Existing Sources

Massachusetts Hazardous Substances List

Michigan Permissible Exposure Limits



# Safety Data Sheet

REMA TIP TOP

Product #s: 5252303, 5252327, 5252334

SDS #: RTT-IND-106

Rev. # 4

Rev. Date: 6/292017

Minnesota Hazardous Substances  
Minnesota Permissible Exposure Limits  
Nebraska Hazardous Air Pollutants  
New Jersey RTK Hazardous Substances List/TCPA Extremely Hazardous Substances List  
New York List of Hazardous Substances  
Ohio Toxic Air Contaminants  
Oklahoma Toxic Air Contaminants  
North Carolina TAP Emissions Rates Requiring a Permit  
Pennsylvania Hazardous Substances List  
Rhode Island Toxic Air Contaminants  
Tennessee Permissible Exposure Limits  
Vermont Hazardous Air Contaminants/Permissible Exposure Limits  
Washington Permissible Exposure Limits for Airborne Contaminants.  
West Virginia Toxic Air Pollutant List  
Wisconsin hazardous Air Contaminants

**Note:** Entries under Section 15 are not intended to be all inclusive of Federal and State laws and regulations. Please consult the appropriate agencies for further clarification of any requirements.

## 16. OTHER INFORMATION

This SDS conforms to the OSHA Hazard Communication Standard 1910.1200 published in the Federal Register March 26, 2012

### **MEDICAL EMERGENCIES:**

Call CHEMTREC 24 hours a  
Day for emergency information  
800-424-9300

### **FOR ANY OTHER INFORMATION:**

REMA TIP TOP - NORTH AMERICA  
240 Pegasus, 2<sup>nd</sup> Floor  
NORTHVALE, NJ 07647  
201-256-8200

**NOTICE:** REMA TIP TOP NORTH AMERICA believes that the information contained on this safety data sheet is accurate. The suggested procedures are based on experience as of the date of publication. They are not necessarily all-inclusive, nor fully adequate in every circumstance. Also, the suggestions should not be confused with, nor followed in violation of, applicable laws, regulations, rules or insurance requirements.

**NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE.**