



Remagrip CK-X Ceramic Lagging Questionnaire

Rema Tip Top North America, Inc.
1500 Industrial Blvd.
Madison, Georgia 30650

Ph. #: (800) 334-7362 Fax: (706) 752-4015

Customer: _____

Contact: _____

Phone: _____

Fax: _____

Address: _____

1. Purpose of Ceramic Lagging:

- Against slippage
- Improved belt tracking
- Improve coefficient of friction
- Against caking
- Against noise
- Other Reason: _____

2. Pulley Dimensions:

Pulley Diameter: _____

Pulley Width: _____

- Straight face pulley
- Crowned center of pulley
- Crowned edges of pulley

3. Pulley Type:

- Drive pulley
Degree of Wrap: _____
- Snub pulley
- Take-up pulley
- Tail pulley
- Other: _____



Remagrip CK-X Ceramic Lagging Questionnaire

Page 2

4. Pulley Designation:

Drum Surface: New Lined
 Rusty Damaged

Drive Horsepower: _____

Soft Start: Yes No

Operating Time: _____
(hours/day ; days/week) _____

Operating Conditions:

Dry Wet
 Wet & Muddy Corrosive

5. Belt Designation:

Manufacturer: _____

P.I.W. Rating: _____

Belt Width: _____

Total Belt Thickness: _____

Top Cover Thickness: _____

Bottom Cover Thickness: _____

Belt Surface: New Damaged
 Worn Out

Belt Splice: Hot Splice Cold Splice
 Mechanical Splice

Belt Trough Angle: _____

Trough Transition Distance: _____

Belt Speed: _____

Belt Length: _____



Remagrip CK-X Ceramic Lagging Questionnaire

Page 3

6. Material Conveyed:

Type of Material: _____

Size of Material: _____

Composition of Material: _____

Tons per Hour: _____

Specific Weight of Material: _____

Humidity %: _____

Oil Content or Chemicals Present: _____

Constant Operating Temperature: _____ Peak Temp.: _____

7. System Details:

Conveyor I.D. Number: _____

Incline

Decline

Horizontal

Type of Take-up: _____

Take-up Weight: _____

8. Sketch of System: